

Technical Data

K-Trade
Great Quality Flooring

	Standard	Result
Size	Planks Tiles	915mm x 152mm (36" x 6") 305mm x 305mm (12" x 12")
Thickness	EN 428	2.0mm
Wear layer	EN 429	0.3mm
Floor Coverage	3.34 square metres per box	
Number of Planks or Tiles per box	24 Planks 36 Tiles	
Guarantee*	Commercial Domestic	6 Years 10 Years
Bevelled edge		No
Standards	EN 649	Pass
Classification	EN 685	31: Commercial moderate 23: Domestic heavy
Reaction to fire	EN 13501-1 EN ISO 9239-1 EN ISO 11925-2	Bfl-S1 ≥8kw/m ² Pass
Slip resistance	EN 13893 BS 7976 DIN 51130	DS Dry: 64 Wet: 30 R9
Staining resistance	EN 423	Class 0
Light fastness	ISO 105-B02	≥ 6 < 8
Abrasion resistance	EN 660-2	Group T
Dimensional stability	EN 434	≤ 0.25% Pass
Acoustic impact noise reduction	EN ISO 717-2 EN ISO 140-8	ΔL _w = 1 db
Electrical behaviour body voltage	EN 1815	Pass
Indentation - residual	EN 433	≤ 0.1mm
Castor chair continuous use	EN 425	Pass
Thermal conductivity	ISO 8302 Suitable for underfloor heating - max 27°C.	0.0100m ² /KW
Adhesive	Acrylic, Epoxy, High Temperature, Pressure Sensitive adhesive suitable	
Recycling		100% Suitable

*Subject to terms and to fitting to industry standard BS 8203.

The samples contained in this shade card are cut from actual product and we take every care to ensure they are an accurate representation, however slight colour variations may occur.

We reserve the right to amend, change or discontinue the designs at any time without notice.

