

FSA Versatile

SPECIFICATION

<i>Product definition</i>	Tufted Plain Level Loop Tile
<i>Pile Material</i>	100% Polypropylene
<i>Pile Yarn Weight</i>	545g/m ² ± 5%
<i>Total Weight</i>	4200g/m ² ± 5%
<i>Pile Height</i>	2,8 mm ± 0,3 mm
<i>Total Thickness</i>	6,2 mm ± 0,3 mm
<i>Gauge/Ends per 10cm</i>	39.4
<i>Tufts per m2</i>	168,100 ± 5%
<i>Backing Type</i>	Graphlar
<i>Style number</i>	6049300004
<i>Wear Classification</i>	EN 1307:31 Contract Moderate
<i>Radiant panel</i>	(EN ISO 9239/1) Euroclass Cfl S1 (EN ISO 13501)
<i>Hot Metal Nut</i>	Pass, low radius of effects of ignition (BS 4790)
<i>Castor Chair Rating</i>	
<i>Dimensional Stability</i>	≤ 0,2% (ISO 2551 / EN 986)
<i>Vertical Electrical Resistance</i>	
<i>Colour Fastness - Light</i>	5-6 (ISO 105/B02)
<i>Tiles per Box</i>	20 - 5 m ² (50 x 50 cm ± 0,2%)

